

Sanimarin Maxlite +

COMPACT RANGE

..... IDEAL FOR SMALL SPACES, ADAPTS TO ALL CONFIGURATIONS

A Saniflo unit to replace your manually-operated WC, regardless of its original configuration.



TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	0,007 Ah (12 V) and 0,004 Ah (24 V) per second (see detail p.26)
WATER CONSUMPTION	Quantity decided by the user
WATER USE	- Sea pump included in the system - Caution : Do not connect the MAXLITE+ toilet to an onboard drinking water or pressurised water system
WEIGHT	8 kg

1 CONTROL SYSTEM



The electric switch Comfort

04

05



Features SFA macerating technology (stainless steel blade)



Easily replaces a hand pumped toilet



Reversible motor/pump unit for right or left hand installation



Enables variable positioning of the bowl



External water supply (integrated pump)



Soft close seat



Ultra-light material used for bowl construction

TECHNICAL VIEW



- Sea pump included in the system
- An additional impeller included in the accessory bag

+ Order your maintenance kit separately
Ref. : KITTURBINEMAXLITE



DIMENSIONS (mm)

