

# Sanimarin 31

COMPACT RANGE

..... SANIMARIN BESTSELLER .....

Thanks to its compact footprint this model fits easily into confined spaces.



## TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	Dependent upon the control system (see detail p.26)
WATER CONSUMPTION	Dependent upon the control system from 1.2 L to 2.4 L
WATER USE	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11L/min
WEIGHT	17 kg


## 4 CONTROL SYSTEMS



The electric switch Comfort



Button Comfort Plus



Button Comfort Luxe



The electronic keyboard Luxe

08

09



Mounting on a raised step



Small dimensions



Connection to the pressurised water onboard



Easy to use



Quiet



Soft close seat

## TECHNICAL VIEWS



Discharge downwards



Other options for discharge

## DIMENSIONS (mm)

