

Sanimarin Exclusive Medium

QUIET RANGE

The most luxurious of the range.



16

..... QUIET AND MODERN DESIGN

TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	Dependent upon the control system (see detail p.26)
WATER CONSUMPTION	Dependent upon the control system from 1.2 L to 2.4 L
WATER USE	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11L/min
WEIGHT	26 kg


4 CONTROL SYSTEMS



The electric switch Comfort



Button Comfort Plus



Button Comfort Luxe



The electronic keyboard Luxe

17



Comfortable



Contemporary design



Vertical back line



A 360° powerful flushing system



Installation distance from black water tank



Quiet
Acoustic pressure : 52 dB(A)

TECHNICAL VIEWS



Exists in a combined toilet/bidet version



Sanimarin Exclusive Medium Bidet delivers economy and space savings thanks to the clever design of the automatic WC combined with the bidet.

DIMENSIONS (mm)

