

# Sanimarin Exclusive Short

COMPACT RANGE

New clean lines for the short model.



12

..... COMPACT AND MODERN DESIGN .....

## TECHNICAL FEATURES

|                             |   |
|-----------------------------|---|
| PUMPING HEIGHT              | 3 m   |
| HORIZONTAL PUMPING DISTANCE | 30 m  |
| NON RETURN VALVE            | Integrated  |
| OUTLET DIAMETER             | 38 mm or 25 mm  |
| SUPPLY VOLTAGE              | 12 V or 24 V DC   |
| MOTOR POWER                 | 300 W (12 V), 360 W (24 V)  |
| ELECTRICITY CONSUMPTION     | Dependent upon the control system (see detail p.26)   |
| WATER CONSUMPTION           | Dependent upon the control system from 1.2 L to 2.4 L   |
| WATER USE                   | - Onboard freshwater (integrated solenoid valve) or outside pressurised water<br>- Minimum pressure of supplied water 1.7 bar<br>- Recommended pump flow rate 11L/min |
| WEIGHT                      | 21 kg   |


## 4 CONTROL SYSTEMS



The electric switch Comfort



Button Comfort Plus



Button Comfort Luxe



The electronic keyboard Luxe

13



Vertical back line



Comfortable



Contemporary design



A 360° powerful flushing system



Easy to use



Quiet

## TECHNICAL VIEWS



Discharge downwards



Other options for discharge

## DIMENSIONS (mm)

