

Sanimarin 43

QUIET RANGE

With its pure and simple lines, it fits easily into all spaces.



14

..... COMFORTABLE AND FUNCTIONAL

TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	Dependent upon the control system (see detail p.26)
WATER CONSUMPTION	Dependent upon the control system from 1.2 L to 2.4 L
WATER USE	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11L/min
WEIGHT	23 kg


4 CONTROL SYSTEMS



The electric switch Comfort



Button Comfort Plus



Button Comfort Luxe



The electronic keyboard Luxe

15



Features SFA macerating technology (stainless steel blade)



Vertical back line



Installation distance from black water tank



Connection to the pressurised water onboard



Quiet Acoustic pressure : 52 dB(A)



Easy to use



Soft close seat

TECHNICAL VIEW



DIMENSIONS (mm)

