

Sanimarin 32

COMPACT RANGE

Easy to install against a vertical partition.



10

..... COMPACT AND COMFORTABLE

TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	Dependent upon the control system (see detail p.26)
WATER CONSUMPTION	Dependent upon the control system from 1.2 L to 2.4 L
WATER USE	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11L/min
WEIGHT	19 kg


4 CONTROL SYSTEMS



The electric switch Comfort



Button Comfort Plus




Button Comfort Luxe



The electronic keyboard Luxe

11



Mounting on a raised step



All the system integrated in the foot



Vertical back line



Connection to the pressurised water onboard



Quiet



Soft close seat

TECHNICAL VIEWS



Discharge downwards



Other options for discharge

DIMENSIONS (mm)

