



..... Sanimarin Exclusive Medium

THE MOST LUXURIOUS OF THE RANGE.



20

..... QUIET AND MODERN DESIGN

TECHNICAL FEATURES

Pumping height	3 m
Horizontal pumping distance	30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Supply voltage	12 V or 24 V DC
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	Dependent upon the control system (see detail p.30)
Water consumption	Dependent upon the control system from 1.2 L to 2.4 L
Water use	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11 L/min
Weight	26 kg

REFERENCES

DESIGNATION	CODE	EAN
Sanimarin Exclusive Medium Comfort 12 V	SNEXCLM12VLC	3308815072937
Sanimarin Exclusive Medium Comfort 24 V	SNEXCLM24VLC	3308815072944
Sanimarin Exclusive Medium Plus 12 V	SNEXCLM12VLC	3308815072951
Sanimarin Exclusive Medium Plus 24 V	SNEXCLM24VLC	3308815072968
Sanimarin Exclusive Medium Premium 12 V	SNEXCLM12VPREMIUM	3308815078038
Sanimarin Exclusive Medium Premium 24 V	SNEXCLM24VPREMIUM	3308815078045
Sanimarin Exclusive Medium Luxe 12 V	SNEXCLM12V	3308815013244
Sanimarin Exclusive Medium Luxe 24 V	SNEXCLM24V	3308815013251

4 CONTROL SYSTEMS



Electric switch
Comfort



Pneumatic button
Plus



Electric button
Premium



Electronic keyboard
Luxe

21




Features SFA
macerating technology
(stainless steel blade)



Comfortable



Contemporary
design



Vertical
back line



A 360° powerful
flushing system



Installation distance
from black water tank



Quiet
Acoustic pressure :
52 dB(A)

TECHNICAL VIEW



DIMENSIONS (MM)

