



.... Sanimarin Exclusive Short

NEW CLEAN LINES FOR THE SHORT MODEL.



16

..... COMPACT AND MODERN DESIGN

TECHNICAL FEATURES

Pumping height	3 m
Horizontal pumping distance	30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Supply voltage	12 V or 24 V DC
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	Dependent upon the control system (see detail p.30)
Water consumption	Dependent upon the control system from 1.2 L to 2.4 L
Water use	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11 L/min
Weight	21 kg

REFERENCES

DESIGNATION	CODE	EAN
Sanimarin Exclusive Short Comfort 12 V	SNEXCLS12VLC	3308815072814
Sanimarin Exclusive Short Comfort 24 V	SNEXCLS24VLC	3308815072821
Sanimarin Exclusive Short Plus 12 V	SNEXCLS12VLCP	3308815072838
Sanimarin Exclusive Short Plus 24 V	SNEXCLS24VLCP	3308815072845
Sanimarin Exclusive Short Premium 12 V	SNEXCLS12VPREMIUM	3308815077895
Sanimarin Exclusive Short Premium 24 V	SNEXCLS24VPREMIUM	3308815077901
Sanimarin Exclusive Short Luxe 12 V	SNEXCLS12V	3308815013220
Sanimarin Exclusive Short Luxe 24 V	SNEXCLS24V	3308815013237

4 CONTROL SYSTEMS



Electric switch
Comfort



Pneumatic button
Plus



Electric button
Premium



Electronic keyboard
Luxe

17



Vertical
back line



Comfortable



Contemporary
design



A 360° powerful
flushing system



Easy to use



Quiet

TECHNICAL VIEWS



Discharge
downwards



Other options
for discharge

DIMENSIONS (MM)

