# **COMPACT RANGE**

## Sanimarin Maxlite •

A SANIFLO UNIT TO REPLACE YOUR MANUALLY-OPERATED WC, REGARDLESS OF ITS ORIGINAL CONFIGURATION.



### **♦** TECHNICAL FEATURES

Pumping height	3 m	
Horizontal pumping distance	30 m	
Non return valve	Integrated	
Outlet diameter	38 mm or 25 mm	
Supply voltage	12 V or 24 V DC	
Motor power	300 W (12 V), 360 W (24 V)	
Electricity consumption	0,007 Ah (12 V) and 0,004 Ah (24 V) per second (see detail p.30)	
Water consumption	Quantity decided by the user	
Water use	<ul> <li>Sea pump included in the system</li> <li>Caution: do not connect the MAXLITE+ toilet to an onboard drinking water or pressurised water system</li> </ul>	
Weight	8 kg	

### **OREFERENCES**

**O** TECHNICAL VIEW

- Sea pump included in the system - An additional impeller included in the accessory bag

DESIGNATION	CODE	EAN
Sanimarin Maxlite Plus 12 V	SBMPLUS12V	3308815076454
Sanimarin Maxlite Plus 24 V	SBMPLUS24V	3308815076461

# 1 CONTROL SYSTEM



macerating technology (stainless steel blade)





a hand pumped

toilet



right or left hand

installation

Reversible motor/ pump unit for



positioning

of the bowl





(integrated pump)





Order your maintenance kit separately REF.: KITTURBINEMAXLITE used for bowl construction

### **ODIMENSIONS (MM)**



