



# .... Sanimarin Maxlite +S

THANKS TO THE USE OF PRESSURISED WATER ON BOARD, THIS QUIET TOILET OFFERS MAXIMUM COMFORT. BEING ULTRA-EFFICIENT, IT CAN BE INTEGRATED INTO ALL TYPES OF CONFIGURATIONS.



10

..... MAXIMUM COMFORT .....

## TECHNICAL FEATURES

<b>Pumping height</b>	3 m
<b>Horizontal pumping distance</b>	30 m
<b>Non return valve</b>	Integrated
<b>Outlet diameter</b>	38 mm or 25 mm
<b>Supply voltage</b>	12 V or 24 V DC
<b>Motor power</b>	300 W (12 V), 360 W (24 V)
<b>Electricity consumption</b>	0,007 Ah (12 V) and 0,004 Ah (24 V) per second (see detail p.30)
<b>Water consumption</b>	Quantity decided by the user
<b>Water use</b>	Integrated solenoid valve for connection to the pressurized water system on board.
<b>Weight</b>	8 kg

## REFERENCES

DESIGNATION	CODE	EAN
Sanimarin Maxlite Plus S 12 V	SBMPLUS12VEV	3308815077840
Sanimarin Maxlite Plus S 24 V	SBMPLUS24VEV	3308815077857

### 1 CONTROL SYSTEM



Electric switch Comfort

11



Connection to the pressurised water onboard



Easy to use



Enables variable positioning of the bowl



Reversible motor/pump unit for right or left hand installation



Soft close seat



Ultra-light material used for bowl construction

## TECHNICAL VIEW



Solenoid valve included

## DIMENSIONS (MM)

