

SANIMARIN MAXLITE + / MAXLITE +S

REDUCED HEIGHT



MADE IN FRANCE

An SFA unit to replace your manually-operated WC.

MAXLITE +

Sea pump included in the system for external water supply

MAXLITE +S

Integrated solenoid valve for connection to the pressurized water system on board.



Ultra-light material used for bowl construction



Enables variable positioning of the bowl



Reversible motor/pump unit for right or left hand installation




Removable soft close seat





CONTROL SYSTEM
(refer to page 20 for details)

Comfort



DIMENSIONS
(mm)



TECHNICAL FEATURES

Discharge parameters	Vertical : 3 m / Horizontal : 30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	0,007 Ah (12 V) and 0,004 Ah (24 V) per second (details on page 5)
Water consumption	Quantity decided by the user
Water use	Maxlite + Sea pump included in the system for external water connection Maxlite +S Integrated solenoid valve for connection to the pressurized water system on board

REFERENCES		
DESIGNATION	CODE	EAN
Sanimarin Maxlite + Comfort 12 V	SBMPLUS12V	3308815076454
Sanimarin Maxlite + Comfort 24 V	SBMPLUS24V	3308815076461
Sanimarin Maxlite + S Comfort 12 V	SBMPLUS12VEV	3308815077840
Sanimarin Maxlite + S Comfort 24 V	SBMPLUS24VEV	3308815077857